

Super Tractor Oil Universal (STOU)

Traction

SAE 10W40



Product Description

Goodyear Traction STOU 10W-40 is semisynthetic extra high performance premium multi-functional oil specially formulated for use in agricultural equipment, engines, transmissions, and differentials with wet brake system and integrated hydraulic system. The product can be used for total tractor lubrication and meets the requirement of many tractor manufacturers.

Benefits

Goodyear Traction STOU 10W40 provides the following benefits:

- Wear protection, delivers wear protection of high - load drives, gears and bearings through stable oil film. Reduces maintenance costs.
- Reduces deposits, extends seal life, and increases service life of equipment and lubricant
- Synthetic components. High thermal stability ensures reliable engine operation over a wide temperature range, extending lubricants life
- Easier engine start-up, reduced wear in critical valve train and good hydraulic response
- Compatibility with seal materials. Good compatibility with sealing materials and non - ferrous metals used in agricultural machinery

Typical Characteristics

Traction-STOU	10W40
API	CD/SE
Specific Gravity @ 15°C	0.8700
Flash Point, °C	28.0
Pour Point, °C	-36
Viscosity at 40°C, cSt	100.45
Viscosity at 100°C,cSt	14.5
Viscosity Index	140

Application

Goodyear Traction STOU 10W-40 is designed for use in engines and gearboxes, oil bath clutch and brake systems, axles and differentials, hydraulic systems of agricultural equipment.

Blended from synthetic components and efficient additives, the oil exhibits high performance characteristics and ensures reliable operation of agricultural machinery.

Properties

Its carefully elaborated formula allows it to be used in both internal combustion engines (including turbocharged engines) and in the different elements of tractors and agricultural machinery (transmissions, final controls, wet brakes, clutches and hydraulic systems).



PERFORMANCE LEVEL- MEETS

- ACEA E3 , Allison C-4
- API CD/SE, CD/SF, CE/SF, CF, CF-4, CG-4, API GL-4
- Caterpillar TO-2 , CCMC D4
- Fiat AF87 , Ford New Holland NH 8209203
- Ford WSS-M2C159B/C, WSS-M2C86B ,
- MAN 271 , Massey Ferguson CMS M1144
- Massey Ferguson CMS M1145 (approved) ,
- New Holland NH O24C
- John Deere JDM J27
- Sauer Sunstrand/Danfoss Hydro Static Trans Fluid
- Sperry Vickers/Eaton I-280-S
- Sperry Vickers/Eaton M2950S
- ZF TE-ML 05K, 06B, 06C, 07B, 07D

Typical physical characteristics of Traction STOU are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Health & Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from your Goodyear lubricants sales office, or via the Internet on www.goodyearlubricants.me



GOODYEAR LUBRICANTS (MENA)
ALONSA ELECTRIC GULF FZCO
PLOT NO. S10717, JEBEL ALI, UAE
www.goodyearlubricants.me